

1. Item Reference		2. Specifications Required	6. Quantities
			TOTAL all deliveries
0 GENERAL			
0.1	Common technical standards / Certifications:	<p>All proposed items and its materials must comply with applicable norms and regulations in force at the tender submission deadline.</p> <p>All items must comply to the NF Environnement Ameublement and NF Office Excellence Certifié (OEC) or set of equivalent certifications.</p> <p>All certifications, in particular also the complementary equivalences, must be included within the tender submission.</p>	
		If not specified differently, measurement deviations and tolerances are to be according to applicable norms.	
		If not specified differently, the standard height of desks and tables must comply with current regulations (H735mm).	
0.2	Care and maintenance:	<p>The finishings, surface coverings, materials, coatings and/or fabrics must be shock resistant and treated to prevent any liquid impregnation (ink, coffee, etc.) or reverberations. They must be easy to clean using just a damp cloth.</p> <p>The tenderers must provide a care and maintenance instruction manual for all of the items of furniture alongside their tender.</p>	
0.3	Technical description:	<p>The items of furniture proposed by the tenderers must be plain, elegant and robust.</p> <p>All of the items of furniture provided under the present lot must match each other: coherent series and shapes and the same finishings within a common or identical colour palette.</p> <p>All items that require adjustments or connections are required to contain manuals. All manuals are to be delivered in two languages – English and French.</p> <p>For an ergonomics training and to assist in adequate seat and desk adjustments of all delivered items, the tenderer must come on site within the first three months after each delivery date.</p>	
0.4	Tender Specifications:	All of the tenders specification's references are to be considered.	
1 OFFICE SPACES			
1.1 Desks			
1.1.1	Management Desk 20 - Electrically Prepared	<p>PT1 <u>finish</u>: desk with a high pressure laminate (HPL) or high resistance melamine</p> <p>preferred colour: white, refer to Annex 1.3</p> <p><u>dimensions</u>: primary desk L2000 mm x D1000 mm</p> <p>credenza: L800 x D600 at the same height as the primary desk</p> <p><u>structure / legs</u>: free-standing structure with loop type legs fitted out with height adjusters, enabling it to adjust to the flatness of the floor.</p>	4

			<p><u>privacy / modesty screens</u>: for the leg room: yes, for the primary desk for the work surface: no</p>	
			<p><u>cable management</u>: both the desk and the credenza must include a cable path / conduit to enable cables to run horizontally underneath it. The main surface must be equipped with 2 cable grommets prepared to access and connect two electricity extension cords up to 4 plugs each as well as networking cables.</p>	
			<p>The credenza must be equipped with a unit composed of 1 plug socket + 1 charging USB up to 2.1A + 1 RJ45 + its cables (electricity: to the main desk, networking Cat 6A: 7,5m).</p>	
1.1.2	Assistants office desk 18 - Electrically Prepared	PT2	<p><u>finish</u>: desk with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer to Annex 1.3 <u>dimensions</u>: L1800 mm x D800 mm</p>	3
			<p><u>structure / legs</u>: structure with laterally centered legs allowing side clearance for leg room. electrical height adjustment, providing heights from around 650mm to 1250mm. The electrical adjustment must be quick and very easy to use. Sliding surface to allow access to cable management</p>	
			<p><u>privacy / modesty screens</u>: for the leg room: yes for the work surface: prepared for its mounting without hindering its height adjustment nor the sliding movement of the surface</p>	
			<p><u>cable management</u>: includes a cable path / conduit to enable cables to run horizontally underneath it. fitted with a notch (échancrure) to enable cables to pass through vertically to the surface</p>	
1.1.3	Co-workers working desk 16 - Electrically Prepared	PT3	<p><u>finish</u>: desk with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer to Annex 1.3 <u>dimensions</u>: L1600 mm x D800 mm</p>	166
			<p><u>structure / legs</u>: structure with laterally centered legs allowing side clearance for leg room. electrical height adjustment, providing heights from around 650mm to 1250mm. The electrical adjustment must be quick and very easy to use. Sliding surface to allow access to cable management</p>	
			<p><u>privacy / modesty screens</u>: for the leg room: no for the work surface: prepared for its mounting without hindering its height adjustment nor the sliding movement of the surface</p>	
			<p><u>cable management</u>: includes a cable path / conduit to enable cables to run horizontally underneath it. fitted with a notch (échancrure) to enable cables to pass through vertically to the surface</p>	
1.1.4	Co-workers working desk 18 - Electrically Prepared	PT4	<p><u>finish</u>: desk with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer to Annex 1.3 <u>dimensions</u>: L1800 mm x D800 mm</p>	35
			<p><u>structure / legs</u>: structure with laterally centered legs allowing side clearance for leg room. electrical height adjustment, providing heights from around 650mm to 1250mm. The electrical adjustment must be quick and very easy to use. Sliding surface to allow access to cable management</p>	

			<u>privacy / modesty screens</u> : for the leg room: no for the work surface: prepared for its mounting without hindering its height adjustment nor the sliding movement of the surface	
			<u>cable management</u> : includes a cable path / conduit to enable cables to run horizontally underneath it. fitted with a notch (échancrure) to enable cables to pass through vertically to the surface	
1.1.5	Monitoring co-workers desk 14 - Electrically Prepared	PT5	<u>finish</u> : desk with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer to Annex 1.3 <u>dimensions</u> : L1400 mm x D800 mm <u>structure / legs</u> : structure with laterally centered legs allowing side clearance for leg room. electrical height adjustment, providing heights from around 650mm to 1250mm. The electrical adjustment must be quick and very easy to use. Sliding surface to allow access to cable management <u>privacy / modesty screens</u> : for the leg room: no for the work surface: prepared for its mounting without hindering its height adjustment nor the sliding movement of the surface <u>cable management</u> : includes a cable path / conduit to enable cables to run horizontally underneath it. fitted with a notch (échancrure) to enable cables to pass through vertically to the surface	14
1.1.6	Nursery / Infirmary desk 12 - Electrically Prepared	PT6	<u>finish</u> : desk with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer to Annex 1.3 <u>dimensions</u> : L1200 mm x D800 mm tolerance in length: +200mm <u>structure / legs</u> : structure with 4 legs <u>privacy / modesty screens</u> : for the leg room: no for the work surface: no <u>cable management</u> : includes a cable path / conduit to enable cables to run horizontally underneath it. equipped with 2 cable grommets prepared to access and connect two electricity extension cords up to 4 plugs each as well as networking cables.	1
1.1.7	"Hot desk"	ST5	<u>finish</u> : desk with a high pressure laminate (HPL) or high resistance melamine preferred colour: "noisetier", refer also to Annex 1.3 <u>dimensions</u> : L800 mm x D800 mm x H1000 mm H tolerance : +/-25mm, in function of adequate stool height item T90 <u>structure / legs</u> : structure with a central chrome-finished support leg on a square base foot <u>privacy / modesty screens</u> : n/a <u>cable management</u> : n/a	16
1.1 TOTAL				
1.2 Privacy / Modesty screens:				
1.2.1	work surface screen 14	ES14	<u>finish</u> : framed or frameless fabric-covered preferred colour: combination / mix of colours within available colour palette, refer also to Annex 1.3 <u>dimensions</u> : L1400 mm x H500 mm L tolerance: according to item PT5 <u>structure</u> : to mount on desk item PT5. The screen fixing system must be invisible and must not hinder the desk's height from being adjusted, or the horizontal sliding motion of its surface.	10
1.2.2	work surface screen 16	ES16	<u>finish</u> : framed or frameless fabric-covered	176

			preferred colour: combination / mix of colours within available colour palette, refer also to Annex 1.3 <u>dimensions:</u> L1600 mm x H500 mm <u>L tolerance:</u> according to item PT3 <u>structure:</u> to mount on desk item PT3. The screen fixing system must be invisible and must not hinder the desk's height from being adjusted, or the horizontal sliding motion of its surface.	
1.2.3	work surface screen 18]	ES18	<u>finish:</u> framed or frameless fabric-covered preferred colour: combination / mix of colours within available colour palette, refer also to Annex 1.3 <u>dimensions:</u> L1800 mm x H500 mm <u>L tolerance:</u> according to item PT4 <u>structure:</u> to mount on desk item PT4. The screen fixing system must be invisible and must not hinder the desk's height from being adjusted, or the horizontal sliding motion of its surface.	35
1.2.4	acoustic screen - suspended	ESS	<u>finish:</u> framed or frameless fabric-covered acoustic attenuation to be indicated preferred colour: combination / mix of colours within available colour palette, refer also to Annex 1.3 <u>dimensions:</u> L1150 mm x H900 mm <u>L tolerance:</u> according to item AB12 <u>H tolerance:</u> +/- 50mm <u>structure:</u> to be suspended above low cabinets certified suspension system included	66
1.2.5	acoustic screen - mounted on legs	ESP	<u>finish:</u> framed or frameless fabric-covered acoustic attenuation to be indicated preferred colour: combination / mix of colours within available colour palette, refer also to Annex 1.3 <u>dimensions:</u> L800 mm x H1200 mm <u>L tolerance:</u> according to item AB12 <u>H tolerance:</u> +/- 50mm <u>structure:</u> mounted on legs	46
1.2 TOTAL				
1.3 Cabinets				
1.3.1	Management Drawer Cabinet	CM	<u>structure / finish:</u> 3-drawer cabinet on wheels, with a high resistance melamine or high pressure laminate (HPL) finish, to be positioned under the desk PT1 in order to store personal belongings. <u>preferred colour:</u> according to PT1 <u>dimensions:</u> L400 mm x D600 mm x H550 mm <u>L/D/H tolerance:</u> +/-100mm <u>doors / interior:</u> required to include a removable stationery unit (plumier) and to present the same design as item PT1 . <u>locks / keys:</u> a lock with a set of 2 keys to enable centralised locking of all the drawers is requested. Each set of keys must have a unique serial number. <u>wheels:</u> additionally, a 5th anti-tipping wheel for greater stability is requested.	4
1.3.2	Co-workers Drawer Cabinet	CM3	<u>structure / finish:</u> 3-drawer metal cabinet on wheels, to be positioned under desks PT 2 to PT5 in order to store personal belongings. The top must have an High resistance melamine or HPL finish, with the same design and finish as items PT2 to PT5. <u>preferred colour:</u> according to PT1	56

			<p><u>dimensions:</u> L400 mm x D600 mm x H550 mm L/D/H tolerance: +/-100mm</p>	
			<p><u>doors / interior:</u> required to include a removable stationery unit (plumier) and to present the same design as items PT2 to PT5 .</p>	
			<p><u>locks / keys:</u> a lock with a set of 2 keys to enable centralised locking of all the drawers is requested. Each set of keys must have a unique serial number. The tenderer must also provide 2 master keys for general key management, enabling access to all of the cabinets.</p>	
			<p><u>wheels:</u> additionally, a 5th anti-tipping wheel for greater stability is requested.</p>	
1.3.3	Local Storage Unit (Rangement de proximité)	RPT	<p><u>structure / finish:</u> local storage unit, fitted with an extractable drawer spanning its full height, and an integrated stationery unit. The top must have an High resistance melamine or HPL finish, with the same design and finish as items PT2 to PT5.</p>	169
			<p><u>preferred colour:</u> according to items PT2 to PT5</p>	
			<p><u>dimensions:</u> L450 mm x D800 mm x H1125 mm L tolerance: +/-20mm D tolerance: according to items PT2 to PT5 H tolerance: +/-75mm</p>	
			<p><u>doors / interior:</u> full height extractable drawer integrated stationery unit with at least 3 shelves / levels.</p>	
			<p><u>locks / keys:</u> a lock with a set of 2 keys per unit is requested. Each set of keys must have a unique serial number. The tenderer must also provide 2 master keys for general key management, enabling access to all of the cabinets.</p>	
			<p><u>feet:</u> the cabinets must be fitted with 4 height adjusters, enabling them to adjust to the flatness of the floor.</p>	
1.3.4	Management Swing-Door Cabinet	ABPB	<p><u>structure / finish:</u> a low, swing-door cabinet with a high resistance melamine or high pressure laminate (HPL) finish, in the same style and finish as the PT1 desk.</p>	7
			<p><u>preferred colour:</u> according to PT1</p>	
			<p><u>dimensions:</u> L1200 mm x D450 mm x H1000 mm L/D tolerance: +/-50mm H tolerance: +150/-50mm</p>	
			<p><u>structure / doors / interior:</u> swing-doors Each cabinet must be fitted with at least 3 removable / adjustable metal shelves, on which hanging files and folders can be suspended.</p>	
			<p><u>locks / keys:</u> a lock with a set of 2 keys per cabinet is requested. Each set of keys must have a unique serial number.</p>	
			<p><u>feet:</u> the cabinets must be fitted with 4 height adjusters, enabling them to adjust to the flatness of the floor.</p>	

1.3.5	Rolling-Door Office Cabinet A	AB8	<p><u>structure / finish:</u> Single-block metal cabinet with acoustic roller doors, with the same design and finish as items PT2 to PT5.</p> <p>The top must have an high resistance melamine or HPL finish.</p> <p>The back must be smooth and attractive, in the event that they will be used in passageways.</p> <p><u>preferred colour:</u> according to PT2 to PT5</p> <p><u>dimensions:</u> L800 mm x D450 mm x H1000 mm</p> <p>L tolerance: +/-20mm</p> <p>D tolerance: +/- 50 mm</p> <p>H tolerance: +150/-50mm</p> <p><u>doors / interior:</u></p> <p>acoustic-finishing (honeycomb surface) rolling-doors.</p> <p>Each cabinet must be fitted with at least 3 removable / adjustable metal shelves.</p> <p><u>locks / keys:</u> a lock with a set of 2 keys per cabinet is requested.</p> <p>Each set of keys must have a unique serial number.</p> <p>The tenderer must also provide 2 master keys for general key management, enabling access to all of the cabinets.</p> <p><u>feet:</u> the cabinets must be fitted with 4 height adjusters, enabling them to adjust to the flatness of the floor.</p>	3
1.3.6	Rolling-Door Office Cabinet B	AB12	<p><u>structure / finish:</u> Single-block metal cabinet with acoustic roller doors, with the same design and finish as items PT2 to PT5.</p> <p>The top must have an high resistance melamine or HPL finish.</p> <p>The back must be smooth and attractive, in the event that they will be used in passageways.</p> <p><u>preferred colour:</u> according to PT2 to PT5</p> <p><u>dimensions:</u> L1200 mm x D450 mm x H1000 mm</p> <p>L tolerance: +/-20mm</p> <p>D tolerance: +/- 50 mm</p> <p>H tolerance: +150/-50mm</p> <p><u>doors / interior:</u></p> <p>acoustic-finishing (honeycomb surface) rolling-doors.</p> <p>Each cabinet must be fitted with at least 3 removable / adjustable metal shelves, on which hanging files and folders can be suspended.</p> <p><u>locks / keys:</u> a lock with a set of 2 keys per cabinet is requested.</p> <p>Each set of keys must have a unique serial number.</p> <p>The tenderer must also provide 2 master keys for general key management, enabling access to all of the cabinets.</p> <p><u>feet:</u> the cabinets must be fitted with 4 height adjusters, enabling them to adjust to the flatness of the floor.</p>	201
1.3.7	Rolling-Door Office Cabinet C	AH12	<p><u>structure / finish:</u> Single-block metal cabinet with acoustic roller doors, with the same design and finish as items PT2 to PT5.</p> <p>The back must be smooth and attractive, in the event that they will be used in passageways.</p> <p><u>preferred colour:</u> according to PT2 to PT5</p> <p><u>dimensions:</u> L1200 mm x D450 mm x H1980 mm</p> <p>L tolerance: +/-20mm</p> <p>D tolerance: +/- 50 mm</p> <p>H tolerance: +25/-25mm</p>	30

			<p><u>doors / interior:</u> acoustic-finishing (honeycomb surface) rolling-doors. Each cabinet must be fitted with at least 5 removable / adjustable metal shelves, on which hanging files and folders can be suspended.</p>	
			<p><u>locks / keys:</u> a lock with a set of 2 keys per cabinet is requested. Each set of keys must have a unique serial number. The tenderer must also provide 2 master keys for general key management, enabling access to all of the cabinets.</p>	
			<p><u>feet:</u> the cabinets must be fitted with 4 height adjusters, enabling them to adjust to the flatness of the floor.</p>	
1.3.8	Print Point Cabinet	AB10	<p><u>structure / finish:</u> Single-block metal cabinet with acoustic roller doors, with the same design and finish as items PT2 to PT5. The top must have an high resistance melamine or HPL finish. preferred colour: "noisetier", refer also to Annex 1.3 <u>dimensions:</u> L1000 mm x D450 mm x H1000 mm L tolerance: +/-20mm D tolerance: +/- 50 mm H tolerance: +150/-50mm</p>	13
			<p><u>doors / interior:</u> acoustic-finishing (honeycomb surface) rolling-doors. It will be installed in all print points and requires the possibility to place a bookbinder, leaving enough space for users to bind their documents Each cabinet must be fitted with at least 2 removable / adjustable metal shelves to store all of the bookbinding equipment in the space below.</p>	
			<p><u>locks / keys:</u> a lock with a set of 2 keys per cabinet is requested. Each set of keys must have a unique serial number. The tenderer must also provide 2 master keys for general key management, enabling access to all of the cabinets.</p>	
			<p><u>feet:</u> the cabinets must be fitted with 4 height adjusters, enabling them to adjust to the flatness of the floor.</p>	
1.3.9	Monitoring Co-workers Cabinet	AH06	<p><u>structure / finish:</u> Single-block metal cabinet with acoustic roller doors, with the same design and finish as item PT5. preferred colour: according to PT5 <u>dimensions:</u> L600 mm x D450 mm x H1980 mm L tolerance: +/-20mm D tolerance: +/- 50 mm H tolerance: +25/-25mm</p>	26
			<p><u>doors / interior:</u> acoustic-finishing (honeycomb surface) rolling-doors. Each cabinet must be fitted with at least 5 removable / adjustable metal shelves, on which hanging files and folders can be suspended.</p>	
			<p><u>locks / keys:</u> a lock with a set of 2 keys per cabinet is requested. Each set of keys must have a unique serial number. The tenderer must also provide 2 master keys for general key management, enabling access to all of the cabinets.</p>	

			feet: the cabinets must be fitted with 4 height adjusters, enabling them to adjust to the flatness of the floor.	
1.3 TOTAL				
1.4 Shelving				
1.4.1	Metal Shelve A	R10	Metal shelving. Size: approximately H2000 mm x L1000 mm for box archiving, with at least 4 adjustable shelves	50
1.4.2	Metal Shelve B	R12	Metal shelving. Size: approximately H2000 mm x L1200 mm for box archiving, with at least 4 adjustable shelves	49
1.4.3	Shelving Stool	THE	Stool to access shelves in height	13
1.4 TOTAL				
1.5 Whiteboards				
1.5.1	Writing Wall	MEB	Writing and magnetic display wall with approximately H2500 mm x L3000 mm. L tolerance: +/-500mm H tolerance: +/- 50 mm	4
			White enamel, to be mounted on divisional walls of management offices or to substitute those walls.	
			This item is to incorporate a storage system for pens and erasers.	
			A writing kit, a set of magnets and an eraser must be included.	
1.5.2	Foldable Whiteboard	TTE	Three-part triptych-type whiteboard with approximately H1000 x L4000 (in the open position), on a wheeled structure. L tolerance: +/-250mm H tolerance: +/- 250 mm	32
			White enamel, to be placed within the collaborative spaces to enable a visual and interactive coordination and brainstorming.	
			This item is to incorporate a storage system for pens and erasers.	
			A writing kit, a set of magnets and an eraser must be included.	
1.5 TOTAL				
1.6 Accessories / Other				
1.6.1	Waste Paper Basket	PO	Paper Basket / Recycling Bin with a capacity of approximately 15l.	22
			Requires 2 compartments to enable recycling / differentiation of confidentiality levels.	
			To be placed in management offices and meeting rooms. The tenderer is to propose a design and finish which is coherent with item PT1.	
1.6.2	Recycle System	POU	Recycling System bin with a capacity of approximately 60l per type of waste (paper, plastic, organic/indifferentiated).	20
			Requires at least 3 compartments following a colour-code according to the type of waste.	
			To be placed at the Print Points, kitchenettes and social spaces.	
1.6.3	Waste Paper Storage	BOX	Vertical box to be placed on the individual desks, to collect A4 format paper which is to be recycled or destroyed at the end of the day.	206
1.6.4	Coat Rack	PMM / PMC	Coat rack with at least 5 hooks. The tenderer must take care to select hooks that will not damage clothes.	77

			The tenderer must propose a design and a finish which is coherent with the rest of the space (management [PT1], Co-workers [PT2 to PT5], meeting rooms, ...).	
1.6.5	Management Desk Lamp	LB	LED lamp with switch at the base. 3 brightness settings. For management offices. The tenderer must propose a design and a finish which is coherent with the rest of the space, or a chrome finish.	8
1.6.6	Desk Blotter	SOUM	Desk blotter for desks PT1	5
1.6.7	"Boa"-type cable management solution	RC	Articulated and flexible "Boa"-type cable management solution for desks PT1 to PT5, for vertical cable management from the plugs on the wall to the desks' cable trays. The product proposed must take into account the height adjustment of the workstation (approximately 1250mm) and having to host either 4 Cat6 cables or 4 16A electrical cables. The tenderer must propose a system which is quick and easy to install. The design and finish must be coherent with that of the desks.	232
1.6.8	CPU / workstation stand	SUC	CPU stand, to be attached underneath the desk's surface or at its structure, adaptable for use with small CPUs measuring about 17.5cm x 18cm x 3.5cm.	184
1.6.9	Single Monitor Support	BE1	Single support arm for one 24" monitor (up to 5kg). Clamp attachment, with easy adjustment of height, width, depth, angle and direction. The tenderer must propose a common solution with item BE2 and a finish which is coherent with the rest of the space, or a chrome finish.	70
1.6.10	Dual Monitor Support	BE2	Single support arm for two 24" monitor (up to 5kg each). Clamp attachment, with easy adjustment of height, width, depth, angle and direction. The tenderer must propose a common solution with item BE2 and a finish which is coherent with the rest of the space, or a chrome finish.	189
1.6.11	Pencil-holder	ACC1	Pencil-holder for the work surface privacy screen. Coherent colour palette or same colour as the surface of desks PT2 to PT5.	210
1.6.12	Letter / Paper tray	ACC2	Letter tray for the work surface privacy screen. Coherent colour palette or same colour as the surface of desks PT2 to PT5.	210
1.6 TOTAL				
1 GRAND TOTAL				
2 MEETING SPACES				
2.1 Desks				
2.1.1	Fold-away meeting table 14 CR - Electrically Prepared	TRR	<u>finish</u> : surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: "noisetier", refer also to Annex 1.3 <u>dimensions</u> : L1400 mm x D700 mm <u>structure / legs</u> : Fold-away meeting table with laterally centered legs allowing side clearance for leg room. Fitted with four wheels with brakes, adapted to carpet flooring. Linking system to align the tables into various different room configurations. <u>privacy / modesty screens</u> : yes, for the leg room	51

			<p><u>cable management</u>: The desk must include a cable path / conduit to enable cables to run horizontally underneath it. The desk's surface must be equipped with a top access with support and socket housing, composed of 3 230V sockets + 2 free plates which can house 2 x RJ45. It must be possible to connect up to 4 tables in series.</p>	
2.1.2	Fold-away meeting table 14 TR	TRR1	<p><u>finish</u>: surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer also to Annex 1.3 <u>dimensions</u>: L1400 mm x D700 mm</p> <p><u>structure / legs</u>: Fold-away meeting table with laterally centered legs allowing side clearance for leg room. Fitted with four wheels with brakes, adapted to carpet flooring. Linking system to align the tables into various different room configurations. <u>privacy / modesty screens</u>: no <u>cable management</u>: no</p>	23
2.1.3	Barrel-shaped meeting room table - Electrified	TRT8	<p><u>finish</u>: surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer to Annex 1.3 <u>dimensions</u>: Barrel-shaped meeting room table with space for up to 8 people. <u>structure / legs</u>: Single frame structure with a maximum of 6 legs. <u>privacy / modesty screens</u>: no</p> <p><u>cable management</u>: The desk must include a cable path / conduit to enable cables to run horizontally underneath it. The surface must be equipped with 4 top access points with 4 socket housing units, composed of 3 230V plug sockets + 2 x RJ45. Initial connection length of cables >3m.</p>	6
2.1.4	"V"-shaped meeting room table - Electrified	TRV	<p><u>finish</u>: surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: "noisetier", refer to Annex 1.3 <u>dimensions</u>: Meeting room table with space for up to 14 people, composed of 6 surfaces measuring approximately L1400 x D800 positioned in a "V" shape, and a surface which provides an angle suitably adapted for comfortable video projector use.</p> <p><u>structure / legs</u>: Table system's common frame to reduce quantity of legs to a maximum of 18. <u>privacy / modesty screens</u>: yes, for the leg room</p> <p><u>cable management</u>: The desk must include a cable path / conduit to enable cables to run horizontally underneath it. Each of the 7 surfaces must be equipped with 1 top access point that is to house 3 230V plug sockets + 2 x RJ45. Initial connection length of cables >3m.</p>	3
2.1.5	"Cat's tongue" shaped meeting room table - Electrified	TRLC	<p><u>finish</u>: surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: the design must be coherent with item PT1. Refer also to Annex 1.3 <u>dimensions</u>: "Cat's tongue" shaped meeting room table with space for four to five people. <u>structure / legs</u>: single frame structure with 4 legs</p>	4

			<u>privacy / modesty screens</u> : no	
			<u>Cable Management / Media Wall</u> : a combined media wall to place a a 42" screen support is required, including an embedded plug socket housing with at least 3 electrical 230V sockets and a fourth spare space as reserve.	
2.1.6	Round meeting room table - Electrified	TRR4	<u>finish</u> : surface with a high pressure laminate (HPL) or high resistance melamine <u>preferred colour</u> : white, refer also to Annex 1.3 <u>dimensions</u> : D1100 mm, for up to four people D tolerance : +/-25mm <u>structure / legs</u> : central round chrome plate and coherent with item FP and adequate for cable management <u>privacy / modesty screens</u> : n/a <u>cable management</u> : Fitted with a telescopic terminal block with 3 electrical plug sockets and a fourth as reserve. Cables must run through the central base.	21
2.1.7	High meeting room table 20 - Electrically Prepared	TRH20	<u>finish</u> : surface with a high pressure laminate (HPL) or high resistance melamine <u>preferred colour</u> : white, refer to Annex 1.3 <u>dimensions</u> : High meeting room table with space for up to 6 people, measuring L2000 mm x D800 mm x H1050 mm. <u>structure / legs</u> : free-standing structure with loop type legs fitted out with height adjusters, enabling it to adjust to the flatness of the floor. <u>privacy / modesty screens</u> : na <u>cable management</u> : The desk comes fitted with a lateral top access point and a plug socket support / cable tray underneath the surface to host electrical sockets.	4
2.1.8	High meeting room table 32 - Electrically Prepared	TRH32	<u>finish</u> : surface with a high pressure laminate (HPL) or high resistance melamine <u>preferred colour</u> : white, or "noisetier" refer to Annex 1.3 <u>dimensions</u> : High meeting room table with space for up to 8 people, measuring L3200 mm x D800 mm x H1050 mm. <u>structure / legs</u> : free-standing structure with loop type legs fitted out with height adjusters, enabling it to adjust to the flatness of the floor. <u>privacy / modesty screens</u> : na <u>cable management</u> : The desk comes fitted with a lateral top access point and a plug socket support / cable tray underneath the surface to host electrical sockets.	5
2.1 TOTAL				
2 GRAND TOTAL				
3 OFFICE AND MEETING SPACES SEATING				
3.1 Office / Working Chairs				
3.1.1	Management Chair	FT1	Ergonomic office chair with high back or headrest for management offices. <u>materials</u> : seat: leather finish backrest: leather finish headrest (optional): leather finish <u>preferred colour</u> : refer to Annex 1.3 <u>legs / wheels</u> : chrome 5-point base on wheels adapted to carpet flooring	4

			<u>adjustments:</u> Chair fitted with a synchronous mechanism, with lateral back tension adjustment, multi-position locking and anti-slip system. optional headrest adjustable in height and tilt armrests: "4D" seat: adjustable in depth and height backrest: adjustable in height and with lumbar support	
3.1.2	Co-workers' Chair	FT2	Ergonomic office chair with for assistants' offices and for use by all co-workers.	208
			<u>materials:</u> seat: fabric backrest: woven fabric headrest (optional): fabric or composite material preferred colour: combination / mix of colours within available colour palette, refer also to Annex 1.3	
			<u>legs / wheels:</u> chrome 5-point base on wheels adapted to carpet flooring	
			<u>adjustments:</u> Chair fitted with a synchronous mechanism, with lateral back tension adjustment, multi-position locking and anti-slip system. armrests: "4D" seat: adjustable in depth and height backrest: adjustable in height and with lumbar support	
3.1 TOTAL				
3.2 Formal Meeting Room Chairs (Scheduled Meetings)				
3.2.1	Meeting room chair with armrests	FVL	Meeting room chair with armrests for all-day meetings in modular or fixed meeting rooms as well as in the management's offices	204
			<u>materials:</u> seat: fabric backrest: woven fabric preferred colour: adapted to items TRR/TRT8/TRV. The design must be coherent with items FRR and CDP. refer also to Annex 1.3	
			<u>legs / wheels:</u> chrome sled-type base, no wheels	
3.2.2	Fold-up meeting room chair	FRR	Fold-up meeting room chair for modular meeting rooms (conference, training rooms) with a fold-away table and armrest. Stackable along the width of the chair.	139
			<u>materials:</u> seat: fabric backrest: woven fabric preferred colour: The design must be coherent with items FVL and CDP. Refer also to Annex 1.3	
			<u>legs / wheels:</u> chrome base on 4 swivel wheels	
3.2.3	Stackable meeting room chair	CDP	Stackable meeting room chair for training rooms. Optional armrest.	42
			<u>materials:</u> seat: fabric backrest: perforated polypropylene preferred colour: The design must be coherent with items FVL and CDP. Refer also to Annex 1.3	

			<u>legs / wheels</u> : 4 chromed feet without wheels	
3.2.4	Transport trolley	CCDP	Transport trolley for CDP item. Quantity to cover all CDP items <u>materials</u> : frame: metal	8
3.2 TOTAL				
3.3 Chairs for Informal Meeting Spaces (ad-hoc meetings)				
3.3.1	High meeting room stool	T90	Stool with seat height suitable for use with TRH105 meeting tables. Fitted with a footrest bar. <u>materials</u> : seat: fabric backrest: fabric preferred colour: adapted to items TRH105 and ST5. refer also to Annex 1.3 <u>legs / wheels</u> : chrome base adapted for carpet flooring, without wheels	80
3.3.2	Swivel chair	FP	Swivel chair. Fully padded armrests. <u>materials</u> : fabric upholstery preferred colour: suitable for meeting rooms using TRR4 tables and in the management offices. refer also to Annex 1.3 <u>legs / wheels</u> : central round chrome plate or support without wheels	47
3.3.3	Round Pouf	ARR	Round 1-person "pouffe-type" seat for brainstorming areas / smartboard coordination spaces. On hidden wheels, with handle <u>materials</u> : fabric upholstery <u>dimensions</u> : D450 mm x H450 mm D/H tolerance: +/-10mm <u>preferred colour</u> : The design must be coherent with FP and ACR <u>wheels</u> : yes, hidden	89
3.3.4	Square Pouf	ACR	Square 1-person "pouffe-type" seat for "Box"-Type meeting rooms and management offices. On hidden wheels, with handle <u>materials</u> : fabric upholstery <u>dimensions</u> : D450 mm x L450 mm x H450 mm D/L/H tolerance: +/-10mm <u>preferred colour</u> : The design must be coherent with FP and ARR <u>wheels</u> : yes, hidden	28
3.3.5	Acoustic chair	FA	Wrap-around acoustic chair, enabling users to isolate themselves for voice communication <u>materials</u> : fabric upholstery <u>dimensions</u> : <D1100 mm x H1300 mm H tolerance: +200mm/-100mm preferred colour: refer also to Annex 1.3 <u>legs / wheels</u> : central chrome swivel plate or support, without wheels	15
3.3 TOTAL				
3 GRAND TOTAL				
4 INFORMAL, PUBLIC AND SOCIAL SPACES				
4.1 Tables and Desks				
4.1.1	High table 20	TH105	<u>finish</u> : surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, refer to Annex 1.3	5

			<p><u>dimensions</u>: High table for the kitchenette with space for up to 6 people, measuring L2000 mm x D600 mm x H1050 mm.</p> <p><u>structure</u> / <u>legs</u>: free-standing structure with loop type legs fitted out with height adjusters, enabling it to adjust to the flatness of the floor.</p> <p><u>privacy / modesty screens</u>: na</p>	
4.1.2	Round coffee table	TBR	<p><u>finish</u>: surface with a high pressure laminate (HPL) or high resistance melamine</p> <p>preferred colour: white, refer also to Annex 1.3</p> <p><u>dimensions</u>: low desk for kitchenettes, measuring D700 mm x H400mm, for up to four people</p> <p><u>structure</u> / <u>legs</u>: central round chrome plate, coherent with item FPE</p> <p><u>privacy / modesty screens</u>: n/a</p>	5
4.1.3	Square coffee table	TBC	<p><u>finish</u>: surface with a high pressure laminate (HPL) or high resistance melamine</p> <p>preferred colour: white, refer also to Annex 1.3</p> <p><u>dimensions</u>: low desk for management offices and reception / waiting areas, measuring D700 mm x L700 mm x H400mm, for up to four people</p> <p><u>structure</u> / <u>legs</u>: central round chrome plate, coherent with items FP, ACR or with AC, AR, BAN2 and CH1</p> <p><u>privacy / modesty screens</u>: n/a</p>	19
4.1.4	Square high table	THC	<p><u>finish</u>: surface with a high pressure laminate (HPL) or high resistance melamine</p> <p>preferred colour: "noisetier", refer also to Annex 1.3</p> <p><u>dimensions</u>: high desk for reception hall, measuring D700 mm x L700 mm x H1000mm, for up to four people</p> <p>H tolerance: +/-25mm</p> <p><u>structure</u> / <u>legs</u>: central round chrome plate, coherent with item FPE</p> <p><u>privacy / modesty screens</u>: n/a</p>	5
4.1 TOTAL				
4.2 Chairs and Seating				
4.2.1	High shell stool	CHC	<p>Shell stool with seat height suitable for use with TH105 tables.</p> <p>Fitted with a footrest bar.</p> <p><u>materials</u>: suitable for use in kitchenettes</p> <p>shell in polycarbonate or other material. Not padded</p> <p>preferred colour: refer to Annex 1.3</p> <p><u>legs / wheels</u>: chrome base adapted for tile flooring, without wheels</p>	26
4.2.2	Coated Swivel chair	FPE	<p>Coated swivel chair.</p> <p>Fully padded armrests.</p> <p><u>materials</u>: suitable for use in kitchenettes</p> <p>upholstery in stain resilient coated tissue</p> <p>preferred colour: refer to Annex 1.3</p> <p><u>legs/ wheels</u>: central cross-shaped chrome base for tile flooring, without wheels</p>	9
4.2.3	Coated rectangular 2-person pouf	AR	<p>Rectangular 2-person "pouffe-type" seat for reception and waiting spaces.</p> <p><u>materials</u>: upholstery in stain resilient coated tissue</p> <p><u>dimensions</u>: D450 mm x L1100 mm x H450 mm</p> <p>D/H tolerance: +/-10mm</p> <p>preferred colour: The design must be coherent with CH1, BAN2, AC and TBC.</p> <p>Also refer to Annex 1.3</p> <p><u>wheels</u>: no. On pads, adapted to tile and carpeted flooring</p>	9

4.2.4	Coated square pouf	AC	Square 1-person "pouffe-type" seat for reception and waiting spaces and kitchenettes <u>materials</u> : upholstery in stain resilient coated tissue <u>dimensions</u> : D450 mm x L450 mm x H450 mm D/L/H tolerance: +/-10mm preferred colour: The design must be coherent with CH1, BAN2, AR and TBC. Also refer to Annex 1.3 <u>wheels</u> : no. On pads, adapted to tile and carped flooring	15
4.2.5	Lounge chair	CH1	Lounge chair for reception and waiting spaces. Fully padded armrests. <u>materials</u> : fabric upholstery preferred colour: The design must be coherent with BAN2, AC, AR and TBC. Also refer to Annex 1.3 <u>feet / wheels</u> : spider type chrome base, no wheels	11
4.2.6	2-seater bench	BAN2	2-seater bench for reception and waiting spaces. Fully padded armrests. <u>materials</u> : fabric upholstery preferred colour: The design must be coherent with CH1, AC, AR and TBC. Also refer to Annex 1.3 <u>feet / wheels</u> : spider type chrome base, no wheels	11
4.2 TOTAL				
4 GRAND TOTAL				
5 CAFETERIA AND EATING SPACES				
5.1 Tables and Desks				
5.1.1	Round cafeteria / dining table	TR4	<u>finish</u> : surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, the design must be coherent with the items TRC and CRC. Refer also to Annex 1.3 <u>dimensions</u> : D1100 mm x H760mm, for four people H tolerance: +/- 10mm D tolerance : +/-25mm <u>structure / legs</u> : white structure with 4 legs, adapted for tile flooring <u>privacy / modesty screens</u> : n/a	4
5.1.2	Square cafeteria / dining table	TRC	<u>finish</u> : surface with a high pressure laminate (HPL) or high resistance melamine preferred colour: white, the design must be coherent with the items TR4 and CRC. Refer also to Annex 1.3 <u>dimensions</u> : D800 mm x L800 mm x H760mm, for two people H tolerance: +/- 10mm <u>structure / legs</u> : white structure with 4 legs, adapted for tile flooring <u>privacy / modesty screens</u> : n/a	24
5.1 TOTAL				
5.2 Chairs and Seating				
5.2.1	Cafeteria / dining shell chair	CRC	Shell chair with seat height suitable for use with TR4 and TRC tables. Stackable <u>materials</u> : suitable for use in kitchenettes and dinig areas shell in polycarbonate or other material. Not padded preferred colour: combination / mix of colours within available colour palette, refer also to Annex 1.3	62

			<u>dimensions</u> : the seat height must allow for a 250mm +/-10mm to the top of the table and of at least 150mm to the underside of the table rail.	
			<u>legs / wheels</u> : chrome base adapted for tile flooring, without wheels	
5.2 TOTAL				
5 GRAND TOTAL				
6 DECORATION AND PLANTS				
6.1 Plants				
6.1.1	Green wall	MV	Green (plants) wall on wheels. Composed of adapted real plants. Must have integrated artificial lighting, automatic watering and water reservoir tank. <u>dimensions</u> : L5000 mm x H2100 mm L tolerance: -200 mm / +400 mm H tolerance: - 100 mm / +250mm <u>wheels</u> : yes	1
6.1.2	Rectangular Floor Vase	BR	Rectangular self sustaining floor vase with flanged neck in composite material. Contains a real plant, measuring H1200/H1400. Includes a water retention system. <u>dimensions</u> : L900 mm x D400 mm x H500 mm L tolerance: +/-50 mm D tolerance: +/-25 mm H tolerance: +/- 25 mm	7
6.1.3	Square Floor Vase	BC	Square self sustaining floor vase with flanged neck in composite material. Contains a real plant (cane, palm, clump type), measuring H1500/H1700. Includes a water retention system. <u>dimensions</u> : L400 mm x D400 mm x H400 mm L tolerance: +/-25 mm D tolerance: +/-25 mm H tolerance: +/- 25 mm	57
6.1.4	High Floor Vase	BCH	High self sustaining floor vase with flanged neck in composite material. Contains a real plant, measuring H600/H800. Includes a water retention system. <u>dimensions</u> : L400 mm x D400 mm x H750 mm L tolerance: +/-25 mm D tolerance: +/-25 mm H tolerance: - 50 mm / +250 mm	58
6.1 TOTAL				
6 GRAND TOTAL				
7 CHANGING AND LOCKER ROOMS				
7.1 Lockers				
7.1.1	Locker Unit with bench	VES	One-sided locker column composed of 2 individual "L"-shaped lockers. Equipped with 1 hanger rail per locker. Indicated quantities are to occupy 2 walls of 4,80 meters length, each composed of 12 lockers. <u>materials</u> : suitable for use in humid atmospheres / locker changing rooms <u>locker column's dimensions</u> : H1800 mm x L per locker 400 mm x D500 mm H tolerance: +/- 50mm L tolerance: +/-10mm D tolerance: +/-10mm Locked using a padlock-able hasp. Padlock not included	26

		<p><u>base / feet:</u> with bench integrated into each locker column's base. On corrosion protective pads, adapted to tile flooring</p>	
		<p><u>bench dimensions:</u> H400 mm x L1200 mm x D Seat section: 300mm H tolerance: +/-10mm L tolerance: equal to 2 locker columns D tolerance: +/- 10mm</p>	
	7.1 TOTAL		
	7 GRAND TOTAL		
TOTAL NUMBER OF ITEMS / TOTAL PRICE without VAT (HT)			3,997